| Model identifier(s): Scar   | n 1005-B CS   | ;         |           |   |   |                              |                 |           |             |
|---|---|-----------|-----------|---|---|------------------------------|-----------------|-----------|-------------|
| Indirect heating functionality  |   |           |           | No  |   |                              |                 |           |             |
| Direct heat output(kW)  |   |           |           | 6   |   |                              |                 |           |             |
| Indirect heat output(kW)  |   |           |           | N.A                                       |   |                              |                 |           |             |
|   |   |           | Preferred |   | Emissions from space heating at nominal heat output |                              |                 |           |             |
|   |   | fuel      | Model     | PM  | OGC   | CO                           | NO <sub>x</sub> |           |             |
| Fuel  |   |           |           | (Only one)                                | identifier(s)                                       | [X] mg/N                     |                 |           |             |
| Wood logs with moisture content ← 25%                                     |   |           |           | Yes                                       | No  | 22                           | 35              | 895       | 93          |
| Compressed wood with moisture content < 12%                               |   |           |           | No  | No  |                              |                 |           |             |
| Other woody biomass   |   |           |           | No  | No  |                              |                 |           |             |
| Anthracite and dry steam coal   |   |           |           | No  | No  |                              |                 |           |             |
| Hard coke   |   |           |           | No  | No  |                              |                 |           |             |
| Low temperature coke  |   |           |           | No  | No  |                              |                 |           |             |
| Bituminous coal   |   |           |           | No  | No  |                              |                 |           |             |
| Lignite briquettes  |   |           |           | No  | No  |                              |                 |           |             |
| Peat briquettes   |   |           |           | No  | No  |                              |                 |           |             |
| Blended fossil fuel briquettes  |   |           |           | No  | No  |                              |                 |           |             |
| Other fossil fuel   |   |           |           | No  | No  |                              |                 |           |             |
| Blended biomass and fossil fuel briquettes                                |   |           |           | No  | No  |                              |                 |           |             |
| Other blend of biomass and solid fuel                                     |   |           |           | No  | No  |                              |                 |           |             |
| Characteristics when operating with the preferred fuel                    |   |           |           |   |   |                              |                 |           |             |
| Seasonal space heating energy efficiency $\eta_s$ [%] 72                  |   |           |           |   |   |                              |                 |           |             |
| Energy Efficiency Class   |   |           |           | A+  |   |                              |                 |           |             |
| Energy Efficiency Index (EEI)   |   |           |           | 109                                       |   |                              |                 |           |             |
| ltem  | Symbol  | Value     | Unit      | lt.                                       | Symbo   | Symbol Value                 |                 | Unit      |             |
| Heat output   |   |           |           | <b>Use efficiency</b> (NCV as re          |   | ceived)                      |                 |           |             |
| Nominal heat output   | P <sub>nom</sub>  | 6         | kW        | Useful efficiency at nominal heat output  |   | $\eta_{\text{th, nom}}$      | 82              |           | %           |
| Minimum heat output (indicative)  | $P_{min}$   | N.A.      | kW        | Useful effic<br>minimum he<br>output (ind | $\eta_{\text{th, min}}$                             | $\eta_{\text{th, min}}$ N.A. |                 | %         |             |
| Auxiliary electricity consumption Type of heat output/room temperature of |   |           |           |   |   |                              |                 | ontrol (s | select one) |
| At nominal heat output  | el <sub>max</sub>   | x,xxx     | kW        | single stage<br>temperatur                | no room [yes/no                                     |                              |                 | Í         |             |
| At minimum heat output  | el <sub>min</sub>   | x,xxx     | kW        | two or more                               |   | [yes/no]                     |                 | Yes       |             |
| In standby mode   | el <sub>sв</sub>  | x,xxx     | kW        | with mecha<br>temperatur                  | t room  | t room [yes                  |                 |           |             |
|   |   |           |           | with electro                              | perature  | ature [yes/no]               |                 |           |             |
|   |   |           |           | with electro<br>control plus              | perature  | [yes/no]                     |                 |           |             |
|   |   |           |           | with electro                              | perature  | [yes/no]                     |                 |           |             |
|   |   |           |           | Other control options (multiple           |   |                              | ections p       | ossible)  |             |
|   |   |           |           | room temp                                 | •   |                              | s/no]           |           |             |
|   |   |           |           | room tempo                                | , with [yes/no]                                     |                              | s/no]           |           |             |
|   |   | with dist |           |   | nce control option                                  |                              |                 | s/no]     |             |
| Permanent pilot flame p   |   |           |           |   |   |                              |                 |           |             |
| Pilot flame power requirement (if applicable)                             | P <sub>pilot</sub>  | N.A.      | kW        |   |   |                              | 1               |           |             |
| Contact details   | Name and address of the supplier:  Brian Ørum, R&D Manager, Scan A/S, Denmark |           |           |   |   |                              |                 |           |             |
|   |   |           |           |   |   |                              |                 |           |             |